

PORODO



Porodo Multi-Port Wall Socket

SKU: PD-FWCH026

Table of Contents

Features	2
Specifications	2
Disposal	2
Warranty	3
Contact Us	3

Features

1. Short Circuit Protection: The power supply will automatically recover after short circuit faults are resolved.
2. Over Current Protection: The power supply will automatically recover after overcurrent faults are resolved. The protection current must not exceed 3900mA.
3. Operating Temperature: 0 to 40°C, full load, normal operation.
4. Storage Temperature: The product's appearance and functionality remain normal when stored at -20°C to 70°C for up to 48 hours.
5. Outputs: Equipped with two AC outputs and two Type-C outputs.

Specifications

Rated Voltage	250V
Rated Current	13A Max
Rated Power	3250W Max
USB-C1/C2 Output	5V/3A, 9V/3A, 12V/3A, 15V/3A, 20V/2.25A (45W Max)
USB-C1 + USB-C2 Output	22.5W + 22.5W or 10W + 35W (Total: 45W Max)
Operating Temperature	0°C to 40°C
Product Size	64.9×112.9×117.7mm
Weight	210g

Disposal

This product must not be disposed of as unsorted household waste. It is important to separate such waste for proper treatment and recycling, in compliance with local waste management regulations.

Warranty

Products that you buy directly from our **Porodo** website or shop come with a 24-month warranty.

When you buy **Porodo** products from any of our approved sellers, you only get a 12-month warranty. If you want to extend this warranty, go to our website at porodo.net/warranty and fill out the form with your information. Don't forget to upload a picture of the product too. After we've checked and accepted your request, we'll send you an email to confirm that your product's warranty has been extended.

For more info, please check:
[**porodo.net/warranty**](http://porodo.net/warranty)

Contact Us

If you have any questions about this Privacy Policy, please contact us at:

info@porodo.net

Website: **porodo.net**

Service Support: **support@porodo.net**

Instagram: **porodo**