PORODO



Porodo

GaN 25W Dual-Port Wall Charger

SKU: PDFWCH076

Table of Contents

| Overview | 2 |
|----------------|---|
| Warnings | 2 |
| Features | 2 |
| Specifications | 3 |
| Disposal | 3 |
| Warranty | 4 |
| Contact Us | 4 |



The Porodo FWC076 PD charger features GaN technology. It supports major fast charging protocols, is pocket-sized, lightweight, and can charge up to two devices simultaneously.

Warnings

- 1. Do not use with devices requiring more than 25W.
- 2. Do not disassemble the charger.
- **3.**Avoid exposure to heat, fire, or ambient temperatures above 60°C (140°F). Keep out of direct sunlight.
- 4. Prevent short circuits.
- 5. Protect from mechanical shocks or impacts.
- 6. Keep out of reach of children; adult supervision is necessary.
- 7. Keep the charger dry; moisture, rain, and liquids can cause corrosion.
- 8. The charger surface may warm during use; do not cover it to ensure proper ventilation.
- 9. Charging will automatically stop if over-voltage, over-current, or over-temperature protection activates and will resume once conditions are safe.

Features

- **1.** This product features one USB-C port and one USB-A port. It supports USB-C protocols including PD 3.0, PPS, QC 4.0-2.0+, Apple FCP, SCP, Samsung DCP, AFC, VOOC, and PE+, as well as USB-A protocols QC 3.0/2.0, Apple FCP, SCP, Samsung DCP, AFC, VOOC, and PE+. It is compatible with major smartphone brands and other devices using USB-A or USB-C power supply, delivering up to 25W.
- 2. Both ports can be used simultaneously, with the charger distributing power accordingly.

- 3. The charger includes multiple safety features such as input and output over-current protection, over-voltage protection, over-temperature protection, overload protection, short circuit protection, electric surge protection, leakage protection, anti-electromagnetic interference, anti-ripple, and ESD protection.
- 4. This charger operates properly at altitudes up to 2000 meters above sea level.

Specifications

| Model | FWC076 |
|-----------------------|--------------------------------------------|
| Charging Protocols | USB-C:PD3.0,PPS,QC4.0-2.0+, Apple,FCP,SCP, |
| | Samsung,DCP,AFC,V00C,PE+ |
| | USB-A:QC3.0/2.0,Apple,FCP, SCP,Samsung, |
| | DCP,AFC,VOOC,PE+ |
| Input | AC 100V-240V 60~50Hz 0.8Amax. |
| Output | Max 25W |
| | USB-C:5V = 3A 9V = 2.77A 12V= 2.08A |
| | USB-A:5V =3A 9V = 2A 12V = 1.5A |
| | USB-C+USB-A:5V =3A |
| Dimension | 2.72*1.65*1.42inch/69*42*36mm |
| Operating Temperature | 32°F-104°F/0-40°C |

Disposal

This product must not be disposed of as unsorted household waste. It is important to separate such waste for proper treatment and recycling, in compliance with local waste management regulations.





Products that you buy directly from our **Porodo** website or shop come with a 24-month warranty.

When you buy **Porodo** products from any of our approved sellers, you only get a 12-month warranty. If you want to extend this warranty, go to our website at **porodo.net/warranty** and fill out the form with your information. Don't forget to upload a picture of the product too. After we've checked and accepted your request, we'll send you an email to confirm that your product's warranty has been extended.

For more info, please check: porodo.net/warranty

Contact Us

If you have any questions about this Privacy Policy, please contact us at:

info@porodo.net

Website: porodo.net

Service Support: support@porodo.net

Instagram: porodo